



Configuration: 132" BBC
Cab: Day Cab
Engine: Cummins® X15

LONEStar®

- ▶ Local or Regional Applications
- ▶ Van, Bulk, Flatbed or Specialty Haul
- ▶ Fleet or Owner Operator
- ▶ Pick up and Delivery

LoneStar® is good for your business and bad to the bone. Its head-turning exterior proudly recognizes classic International® design heritage, yet LoneStar is engineered to meet today's regional-haul demands for optimal uptime, productivity and performance. The spacious DriverFirst™-inspired cab features intuitive controls, high-visibility gauges and dozens of other smart, driver-tested ideas to keep drivers comfortable and in control. And that bold chrome grille and sleek hood offer more than good looks - the aerodynamic shape delivers greater fuel efficiency than conventional long-nose trucks.





KEY FEATURES:

- ▶ Up to 605 HP and 2,050 lb.-ft. torque with the Cummins® X15
- ▶ Reduced weight, improved aerodynamics and optimized drivetrains provide up to a 3% fuel economy gain over previous models
- ▶ New door, side glass and mirror designs improve lateral visibility and reduce neck strain
- ▶ All-new dash designed for the driver with controls and switch placement optimized by frequency of use
- ▶ Premium gauge cluster designed with driver input is customizable with virtual gauges
- ▶ Bendix® Wingman® Advanced™ Collision Mitigation is standard
- ▶ Easy-access column-mounted shifter integrated with engine braking helps keep hands on the wheel
- ▶ New industry-standard J1939 electrical system architecture and improved harnessing to maximize uptime
- ▶ All-new HVAC system designed for reliability, now includes a high-performance MAX defrost feature
- ▶ Redesigned center console has been ergonomically-refined for improved knee room
- ▶ Advanced classic, aerodynamic design provides improved fuel economy over traditional long-hood conventional



132" BBC SET-FORWARD FRONT AXLE

GVW

- ▶ 52,350 – 60,600 lbs.

Models/BBC/BA

- ▶ 132" BBC / 41" BA

Wheelbase Options

- ▶ 167 - 280"

Axle Configurations

- ▶ 6x4

Rear Axle

- ▶ TANDEM REAR AXLE (6x4)
 - Meritor: 40,000 – 46,000 lbs.
 - Dana Spicer: 40,000 lbs.

Front Axle

- ▶ Hendrickson: 12,350 – 14,600 lbs.
- ▶ Dana Spicer: 12,350 – 14,600 lbs.
- ▶ Meritor: 12,350 – 14,600 lbs.

Frames

- ▶ Heat Treated Alloy Steel 120,000 PSI

Front Suspension

- ▶ Spring Monoleaf: 12,350 – 13,200 lbs.
- ▶ Parabolic Taperleaf: 12,350 – 14,600 lbs.

Rear Suspension

- ▶ AIR TANDEM
 - International: 40,000 lbs.
 - Hendrickson: 40,000 – 46,000 lbs.

Electrical System

- ▶ ALTERNATORS
 - Bosch: 12 Volt, 160 – 200 Amp
 - Leece-Neville: 12 Volt, 160 – 325 Amp
 - Delco Remy: 12 Volt, 165 – 300 Amp
- ▶ BATTERY SYSTEMS
 - International®: 12 Volt 1950 – 3000 CCA
 - Exide: 12 Volt 1950 – 3000 CCA
 - JCI: 12 Volt 2250 – 3000 CCA
 - Fleetrite®: 12 Volt 2800 – 5600 CCA
 - Enersys Odyssey: 12 Volt 4600 CCA

Exhaust System

- ▶ Single canister after-treatment device
- ▶ Frame Mounted Right Side, Under Cab
- ▶ Dual B-pillar Vertical Tailpipes

Brakes

- ▶ Air Drum Brakes with ABS with Optional Automatic Traction Control and Electronic Stability Control
- ▶ Air Disc Brakes with Automatic Traction Control and Electronic Stability Control

Power Steering

- ▶ Sheppard
- ▶ TRW

Engines

- ▶ Cummins® X15: 400 – 605 hp and 1,450 – 2,050 lb.-ft. of torque

Transmissions

- ▶ Eaton®: 10, 13, 18-Speed Manual
- ▶ Eaton UltraShift® PLUS: 13, 16, 18-Speed Automated Manual
- ▶ Eaton Fuller Advantage™ Series: 10-speed

Fuel Tanks

- ▶ 70 – 140 Gallon Dual, Non-Polished or Polished Aluminum, Mounted Back of Cab

Tires

- ▶ Continental, Michelin, Goodyear, Bridgestone

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice. TAD17021 08/15/2017 ©2017 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.